

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 0 688 550 B2**

(12) **NEW EUROPEAN PATENT SPECIFICATION**

(45) Date of publication and mention
of the opposition decision:
07.08.2002 Bulletin 2002/32

(51) Int Cl.7: **A61F 13/15**

(45) Mention of the grant of the patent:
14.04.1999 Bulletin 1999/15

(21) Application number: **95109839.1**

(22) Date of filing: **23.06.1995**

(54) **Disposable diaper equipped with elastic waistband**

Wegwerfwindel mit elastischem Taillenband

Couche jetable avec une ceinture de taille élastique

(84) Designated Contracting States:
BE DE ES FR GB IT NL PT SE

(30) Priority: **23.06.1994 US 264539**

(43) Date of publication of application:
27.12.1995 Bulletin 1995/52

(73) Proprietor: **KIMBERLY-CLARK WORLDWIDE,
INC.**
Neenah, Wisconsin 54956 (US)

(72) Inventor: **Jessup, James Lyle**
Appleton, Wisconsin 54915 (US)

(74) Representative: **Davies, Christopher Robert et al**
Frank B. Dehn & Co.,
European Patent Attorneys,
179 Queen Victoria Street
London EC4V 4EL (GB)

(56) References cited:

EP-A- 0 320 989	EP-A- 0 526 868
EP-A- 0 547 497	WO-A-93/25171
GB-A- 1 520 740	US-A- 4 883 549
US-A- 4 940 464	

EP 0 688 550 B2

Description

[0001] The present invention relates to disposable absorbent garments.

[0002] In the last several years, disposable absorbent garments have become available for use by children in the potty-training stage, and have proved to be extremely popular with mothers and caretakers. A specific example is a training pant comprising a bodyside liner, an outer cover, an absorbent medium between the liner and the outer cover, and side seams that bond portions of the side edges of the pant together to form waist and leg openings.

[0003] One style of training pant has elastic side panels that fit against the hips of the child, and discrete front and back elastic waist strips adjacent the waist opening. The waist strips generally are spaced from the elastic side panels. Such a training pant is disclosed, for example, in EP-A-0 526 868.

[0004] Although these discrete front and back elastic waist strips may provide some gasketing at the front and back of the pant, they are not entirely effective in providing the desired gasketing and fit at the waist resulting in satisfactory waste containment.

[0005] The present invention intends to overcome these problems.

[0006] The object is solved by the disposable garment according to independent claims 1 and 4.

[0007] Further advantages, features, aspects and details of the invention are evident from the dependent claims, the description and the accompanying drawings. The claims are intended to be understood as a first non-limiting approach of defining the invention in general terms.

[0008] The disposable absorbent garment according to the present invention comprises a continuous, selectively elasticized band joined about an opening thereof for improving fit and comfort.

[0009] The above-mentioned and other features of the present invention and the manner of attaining them will become more apparent, and the invention itself will be better understood by reference to the following description of the invention, taken in conjunction with the accompanying drawings, wherein:

Fig. 1 illustrates a front perspective view of one type of a disposable elasticized, absorbent garment incorporating the principles of the present invention;

Fig. 2 illustrates a partially exploded view of Fig. 1 with a continuous, selectively elasticized waistband separated from the garment;

Fig. 3 illustrates a cross-sectional view of Fig. 1 taken along line 3-3 and viewed in the direction of the arrows;

Fig. 4 illustrates an exploded, perspective view of

the garment in Fig. 1 in a partially disassembled, extended flat state;

Fig. 5 illustrates a top plan view of the garment in Fig. 1 in a partially disassembled, extended flat state;

Fig. 6 illustrates a top plan view of the garment in Fig. 1;

Fig. 7 illustrates a cross-sectional view through a waist portion of the garment in Fig. 1;

Figs. 7A-7D illustrate modifications of the view in Fig. 7; and

Fig. 8 illustrates a modification of the garment in Fig. 5.

[0010] Each of the following terms used herein include the following meaning:

[0011] "Composite elastic material" or "composite elastic web" means a multi-layered material having at least one elastic layer joined to at least one gatherable layer at least at two locations wherein the gatherable layer is gathered between the locations where it is joined to the elastic layer. A composite elastic material may be stretched to the extent that the non-elastic material gathered between the bond locations allows the elastic material to extend. This type of composite elastic material is disclosed, for example, by Vander Wielen et al., US-A-4,720,415 issued January 19, 1988.

[0012] "Continuous" means that the described structure is a closed-loop structure. The continuous structure may be unitary, i.e., a one-piece structure, or may be made up of individual elements suitably joined together to form a closed-loop.

[0013] "Disposable" means that the described garment is designed to be used until soiled, either by urination, defecation, or otherwise, and then discarded, rather than being washed and used again.

[0014] "Elastic", "elasticity", "elasticized", or the like, refers to a material or composite material that tends to recover its original size and shape after removal of the force causing the deformation (expressed in %).

[0015] "Elongation" means the ratio of the extension of a material to the length of the material prior to the extension (expressed in percent), as represented by the following:

$$\frac{\text{extended length} - \text{original length}}{\text{original length}} \times 100.$$

[0016] "Extension" means the change in length of a material due to stretching (expressed in units of length).

[0017] "Join", "joining", "joined", or variations thereof, when used in describing the relationship between two or more elements, means that the elements can be con-

nected together in any suitable manner, such as by heat sealing, ultrasonic bonding, thermal bonding, by adhesives, stitching, or the like. Further, the elements can be joined directly together, or may have one or more elements interposed between them, all of which are connected together.

[0018] "Operatively elastically joined" describes the joining of an elastic member to a non-elastic member such that the two joined members exhibit elasticity.

[0019] "Pant body" refers to a garment that has a waist opening and a pair of leg openings, similar to shorts, swim wear, or the like. The described garment may or may not have a manually tearable side seam.

[0020] "Recover", "recovering", or variations thereof, refers to a contraction of an extended material upon termination or removal of a biasing force, or upon suitably treating the material after it has been temporarily inhibited.

[0021] "Temporarily inhibit" means to delay the total recovery of an extended elastic layer (or substrate) or composite elastic material. The delay may be imparted by compressing the extended elastic layer, or by compressing the composite elastic material so that the elastic and gatherable layers are temporarily joined. Partial recovery of a temporarily inhibited elastic layer or composite elastic material may occur immediately after the force is removed, but total recovery of such a temporarily inhibited elastic layer or composite elastic material will require more time than the total recovery of the same material which has not been temporarily inhibited. For example, total recovery of an extended elastic layer or composite elastic material that has not been temporarily inhibited may be instantaneous, whereas the total recovery of a temporarily inhibited elastic layer or composite elastic material may take, for example, from about 5 to about 60 seconds.

[0022] "Total recovery", or variations thereof, refers to a material recovering to generally within about 20 percent of its relaxed, pre-extended dimension.

[0023] Referring primarily to Fig. 1, there is illustrated disposable absorbent garment 10 in the form of a child's training pant. Although garment 10 is illustrated and will be described as a training pant, it can be other types of absorbent garments or articles, such as baby diapers, adult incontinence products, or the like.

[0024] Disposable absorbent garment 10 includes a pant body 12 comprising a front section 14, a back section 16, a crotch section 18, elastic side sections 20, seams 22, a continuous waist opening 24, and a pair of continuous leg openings 26. Each elastic side section 20 includes a front elastic side member 68 (Fig. 5) and a back elastic side member 70, which are joined together at a respective seam 22. Garment 10 further includes a continuous waistborder 30 (Figs. 1 and 2), continuous legborders 38, and a continuous waistband 32. Continuous waistband 32 comprises front waistband member 64 (Fig. 5) and back waistband member 66. Continuous waistborder 30 comprises front waistborder section 42

(Figs. 4, 5) having front edge 44 and back waistborder section 46 having back edge 48. An absorbent structure 28 is suitably incorporated in garment 10 at least at crotch section 18 thereof.

[0025] Pant body 12 includes a topsheet 34 (Fig. 4) and a backsheet 36, which are desirably coincident with one another, although not a requirement of the present invention. Backsheet 36 (Fig. 5) includes a pair of front outer edges 50, front inner edges 52, innermost edges 54, back sloping edges 56, and back outer edges 58.

[0026] Front waistband member 64 (Figs. 4, 5) is suitably joined to front waistborder section 42, and back waistband member 66 is suitably joined to back waistborder section 46. Front and back waistborder sections 42, 46 desirably have respective lengths substantially corresponding to the respective lengths of front and back waistband members 64, 66, and widths substantially corresponding to the respective widths of front and back waistband members 64, 66; length being measured along a line generally parallel to transverse centerline 60 (Fig. 5) and width being measured along a line generally parallel to longitudinal centerline 62. A desired width range of waistband members 64, 66 is between about 1 centimeter to about 8 centimeters, and a more desired range is between about 2 centimeters to about 4 centimeters. In the case where, for example, one or both of the waistband members 64, 66 have some other geometric shape, i.e., not an elongate rectangular shape as illustrated in Figs. 4 and 5, each waistborder section 42, 46 desirably would have substantially the same geometric shape as its respective waistband member 64, 66.

[0027] With reference primarily to Figs. 1 and 5, when garment 10 is folded along a transverse fold-line, which is generally parallel to transverse centerline 60, and pairs of aligned front and back outer edges 50, 58 are joined together to form seams 22, the following construction is accomplished: (i) front waistborder section 42 and back waistborder section 46 form or define continuous waistborder 30; (ii) front waistband member 64 and back waistband member 66 form or define continuous waistband 32; (iii) a front inner edge 52, an innermost edge 54, and a back sloping edge 56 form or define a respective leg opening 26; (iv) and a front elastic side member 68 and a back elastic side member 70 form or define a respective elastic side section 20.

[0028] Garment 10 also comprises a pair of leg elastic members 72 (Fig. 5) that are suitably joined, for example, between topsheet 34 and backsheet 36 (Fig. 4).

[0029] Absorbent structure 28 (Figs. 4 and 5) comprises front absorbent edge 74, back absorbent edge 76, and absorbent side edges 78. As illustrated in Fig. 5, front absorbent edge 74 and back absorbent edge 76 are respectively inboard of front waistband member 64 and back waistband member 66. Similarly, absorbent side edges 78 are inboard of respective leg elastic members 72. By "inboard" is meant that absorbent front edge 74, for example, is closer to transverse centerline 60

than front waistband member 64, and absorbent side edges 78 are closer to longitudinal centerline 62 than leg elastic members 72.

[0030] When garment 10 is properly fitted on the wearer, topsheet 34 faces toward the body of the wearer, and may or may not be the layer that directly contacts the skin. Topsheet 34 can be a liquid permeable, elastic or non-elastic, substantially hydrophobic material, such as a spunbonded web of synthetic polymer filaments. Topsheet 34 can also be a meltblown web or a bonded carded web of synthetic polymer filaments. Suitable synthetic polymers include, for example, polyethylene, polypropylene, and polyesters. Topsheet 34 has a pore size that readily allows the passage therethrough of liquids, such as urine and other body exudates. If desired, topsheet 34 can be treated with surfactants to selectively adjust its degree of wettability, and can also be selectively embossed or perforated with discrete slits or holes extending therethrough. Suitable topsheet materials can have a basis weight between about 10 grams per square meter (g/m^2) to about 26 g/m^2 , and a thickness between about 0.013 centimeters to about 0.064 centimeters. The thickness of the topsheet material can be determined by employing an Ames Bulk Test (ASTM D-1777) performed at a restraining pressure of 1.38 kPa (0.2 psi).

[0031] Backsheet 36, which may or may not be the outermost layer of garment 10, can be liquid permeable or liquid impermeable, and may or may not have breathability, i.e., be vapor permeable. A suitable liquid permeable backsheet 36 is a nonwoven bicomponent web having a basis weight between about 15 g/m^2 to about 50 g/m^2 . The nonwoven bicomponent web may be a spunbond bicomponent web, or a bonded carded bicomponent web. Suitable bicomponent fibers are a wettable, polyethylene/polypropylene bicomponent fiber available from CHISSO Corporation, Osaka, Japan. In this particular bicomponent fiber, the polypropylene forms the core and the polyethylene forms the sheath of the fiber. Other fiber orientations are possible, such as multi-lobe, side-by-side or end-to-end. Another suitable liquid permeable material is a liquid permeable spunbond polypropylene nonwoven web having a basis weight between about 15 g/m^2 to about 50 g/m^2 .

[0032] A suitable liquid impermeable backsheet 36 is a 0.0015 centimeter polyethylene film from Edison Plastics Company, South Plainfield, New Jersey. Backsheet 36 can also be a two-ply laminate, in which the innermost layer can be the above-described liquid impermeable film or any other suitable liquid impermeable layer, and the outermost layer can be the above-described liquid permeable spunbond polypropylene nonwoven web or any other suitable liquid permeable layer. Backsheet 36 desirably has a thickness within the range of about 0.0013 to about 0.0051 centimeters.

[0033] Absorbent structure 28 can comprise any suitable absorbent material, natural or synthetic, or a combination thereof, along with superabsorbent material.

The absorbent material of which absorbent structure 28 is made may also be encased in a tissue wrap (not shown) in order to maintain the integrity of the absorbent material comprising absorbent structure 28. Suitable superabsorbent materials are available from various vendors, such as Dow Chemical Company, Hoechst-Celanesse Corporation, and Allied Colloids, Inc. A suitable natural absorbent material is a wood pulp fluff identified by the trade designation CR1654 from Kimberly-Clark Corporation, Neenah, Wisconsin. One specific absorbent structure 28 that can be suitably used in garment 10 is described in US-A-5,509,915, inventors Hanson et al., which is assigned to the assignee of this application.

[0034] The construction of garment 10 can be accomplished in any conventional manner well known in the art. For example, the structural elements can be joined together in any manner, such as by heat sealing or ultrasonic bonding, or by adhering the elements together with a suitable adhesive. Suitable adhesives can be obtained from Findley Adhesives, Inc., Wauwatosa, Wisconsin, and can be applied in any manner, such as by spraying, slot-coat extrusion, printing, or the like. The applied adhesive can be in any desired configuration, such as continuous or discontinuous beads, continuous or discontinuous swirls, meltblown patterns, spray patterns, or the like.

[0035] Referring to Figs. 1-6, front elastic side members 68 (Fig. 5) can have the same or different geometry from back elastic side members 70. Each front elastic side member 68 and each back elastic side member 70 comprises an elastic layer 80 (Fig. 3, 6) sandwiched between topsheet 34 and backsheet 36. Elastic layer 80 can be any suitable elastic material, one such material being a block copolymer of styrene-ethyl-butadiene-styrene. Other types of materials of which elastic layer 80 can be made are the KRATON® G series from The Shell Chemical Company such as KRA-TON® G-1650, KRA-TON® G-1652, KRATON® GX-1657 and KRATON® G-2740X. The KRATON® D series can also be used, as well as polyester elastomeric materials, polyurethane elastomeric materials, and polyamide elastomeric materials. Elastic layer 80 can be a film, nonwoven web, or ribbons or threads of synthetic or natural rubber arranged, for example, in a spaced, parallel manner.

[0036] Each elastic layer 80 is operatively elastically joined to a portion of either topsheet 34 or backsheet 36, preferably to portions of both topsheet 34 and backsheet 36, in order to provide elasticity to those portions. One example of this is disclosed in EP-A-0 547 497 filed March 25, 1993, inventor Van Gompel et al. Another example of providing elastic side sections 20 is described in US-A-4,940,464, issued July 10, 1990, to inventor Van Gompel et al.

[0037] Still other examples of elastic materials and composites are described in US-A-4,720,415, issued January 19, 1988, to Vander Wielen et al.; US-A-4,657,802, issued April 14, 1987, to Morman; and US-A-4,652,487 issued March 24, 1987, to Morman.

[0038] Each elastic side section 20 in disposable absorbent garment 10 (Fig. 1) can have an elasticity between about 50% to about 250%, desirably an elasticity between about 75% to about 200%, and more desirably an elasticity between about 100% to about 150%.

[0039] Referring primarily to Figs. 2, 4-6, continuous waistborder 30 (Fig. 2) comprises oppositely disposed elastic side segments 82, non-elastic front segment 84, and non-elastic back segment 86. Each elastic side segment 82 includes a portion of a respective elastic side section 20. Non-elastic front segment 84 and non-elastic back segment 86, as illustrated in Fig. 6, include portions of topsheet 34 and backsheet 36. Thus, continuous waistborder 30 (Fig. 2) is partially elastic due to elastic side segments 82.

[0040] Continuous waistband 32 can be an elastomeric, cloth-like, nonwoven fibrous material, such as an elastomeric stretch bonded laminate web or an elastomeric meltblown web. By proper selection of materials, continuous waistband 32 can be rendered temporarily elastically inhibited, such as by compression. Once temporarily elastically inhibited, the elastic material, of which waistband 32 is comprised, can be activated, such as by treating with heat, to recover to a state of elasticity.

[0041] In one specific embodiment, waistband 32 comprises an elastomeric nonwoven fibrous web that is substantially vapor-permeable. Examples of suitable elastomeric nonwoven fibrous webs are described in US-A-4,663,220 issued May 5, 1987, to Wisneski et al. Examples of composite fabrics comprising at least one layer of nonwoven textile fabric joined to a fibrous elastic layer are described in EP-A-0 217032 published on April 8, 1987, inventors J. Taylor et al.

[0042] The composite nonwoven fabrics are commonly referred to as stretch bonded laminates.

[0043] In another embodiment, waistband 32 comprises a composite elastomeric web comprising individual, discrete strips or strands of elastomeric material secured to one or more nonwoven fibrous layers. Such a composite elastomeric web may, for example, comprise an elastomeric meltblown material arranged in a selected pattern of strips and suitably sandwiched and joined between two layers of nonwoven fibrous material. This material, as well as others, is described in US-A-4,861,652 issued August 29, 1989. Still other useful composite elastic materials are described in US-A-4,883,549, issued November 28, 1989.

[0044] One of the innovative features of the present invention is selectively providing portions of continuous waistband 32 (Figs. 1-2) with different elasticities as determined by, for example, the elasticity of elastic side sections 20 and the desired elasticity to be provided to non-elastic front segment 84 and/or non-elastic back segment 86. Another novel feature of the present invention is providing a

[0045] continuous waistband 32 about a continuous waistborder 30 such that it does not substantially restrict

or diminish the elasticity of elastic side sections 20, and can provide a desired elasticity to non-elastic front and back segments 84, 86.

[0046] Following is one example of a selectively elasticized continuous waistborder 30. With reference to Figs. 4 and 5, front and back waistborder sections 42, 46 define continuous waistborder 30 (Fig. 1), and have front and back waistband members 64, 66 suitably joined thereto, respectively. Since the joining of front waistband member 64 to front waistborder section 42 can be identical to the joining of back waistband member 66 to back waistborder section 46, a description only of the former will be given. In this example, each elastic side segment 82 (Fig. 2) has an elasticity of about 180%, i.e., each elastic side segment 82 can be extended 2.8 times its original length. It is desired that non-elastic front segment 84 be given an elasticity different from that of elastic side segment 82.

[0047] Front waistband member 64 (Figs. 4, 5) includes side portions 88 and a recoverable front portion 90 therebetween. It is desired that front waistband member 64 be a unitary structure. However, side portions 88 and front portion 90 can be separate structures suitably joined together to form front waistband member 64. Since elastic side segments 82 (Fig. 2) have an elasticity of about 180%, front waistband member 64 is selected and configured also to have an elasticity of about 180%. Each side portion 88 in Fig. 4 has a length, as measured along centerline 60 (Fig. 5), of about 50 millimeters, and recoverable front portion 90 has a length of about 90 millimeters.

[0048] Front waistborder section 42 in Fig. 4 includes two elastic side segments 82 sandwiching non-elastic front segment 84. Each side segment 82 in Fig. 4 has a length of about 50 millimeters, and front segment 84 has a length of about 150 millimeters. Prior to joining front waistband member 64 to front waistborder section 42, recoverable front portion 90 is elongated about 67%, which results in an extended length of about 150 millimeters. After extending recoverable front portion 90, it is temporarily elastically inhibited such as by, for example, compression, thereby providing front portion 90 with the property of being totally recoverable, i.e., able to return to an elastic condition upon being suitably activated, such as by treating with heat. After front portion 90 has been extended and temporarily elastically inhibited, front waistband member 64 is suitably intermittently joined, such as by ultrasonic, heat, or adhesive point bonding, to front waistborder section 42, such that front portion 90 is joined to front segment 84.

[0049] In a similar manner, back waistband member 66 is joined to back waistborder section 46. Thereafter, disposable absorbent garment 10 is folded along a fold line generally parallel to transverse centerline 60, and front outer edges 50 (Fig. 5) are suitably bonded to back outer edges 58 to form seams 22. Garment 10 is then treated, such as with heat, in order to activate temporarily elastically inhibited front portion 90 and back por-

tion 92. Upon total recovery, front portion 90 will gather non-elastic front segment 84 and back portion 92 will gather non-elastic back segment 86. Depending upon the selection of materials for front and back waistborder sections 42, 46 and front and back waistband members 64, 66, front segment 84 and front portion 90, when joined together, can have an elasticity between about 30% to about 60%.

[0050] It will be appreciated that the elasticity about waist opening 24 of garment 10 (Fig. 1) depends on various factors, such as the types of materials of which waistband 32 and waistborder 30 are comprised, their elastic characteristics, and the like. Thus, continuous waistband 32 will need to be carefully designed and constructed, as to materials and elasticity, so that once it is suitably joined to continuous waistborder 30, front and back segments 84, 86 will be given the desired elasticity.

[0051] Continuous waistband 32 can be suitably joined to continuous waistborder 30 in a number of desired configurations. Fig. 7 illustrates one configuration in which continuous waistband 32 and continuous waistborder 30 are joined together such that top edge 98 of continuous waistband 32 is substantially coplanar with peripheral edge 40 of continuous waistborder 30.

[0052] Fig. 7A is similar to Fig. 7 except that continuous waistband 32 is offset from continuous waistborder 30, such that a portion of waistband 32 extends beyond continuous waistborder 30. In this configuration, top edge 98 extends beyond peripheral edge 40.

[0053] Referring to Fig. 7B, continuous waistband 32 has a folded portion 102 that is folded over peripheral edge 40, such that top edge 98 is on the side of continuous waistborder 30 opposite from bottom edge 100.

[0054] The configuration in Fig. 7C is similar to that in 7B, except that the portion of continuous waistband 32 comprising bottom edge 100 has been folded upon itself to create a C-fold portion 104.

[0055] The configuration in Fig. 7D illustrates continuous waistband 32 having two C-fold portions 104, with the C-fold portion 104 that includes bottom edge 100 being suitably joined to continuous waistborder 30. In this configuration, top edge 98 extends beyond peripheral edge 40.

[0056] Fig. 8 illustrates a modification to disposable absorbent garment 10 illustrated in Fig. 1, in which elastic legbands 106 have replaced leg elastic members 72 and have been suitably joined to legborders 108. An elastic legband 106 can be suitably joined to a legborder 108 in a manner similar to the joining of front waistband member 64 to front waistborder section 42 (Fig. 5).

Claims

1. A disposable garment, comprising:

a pant body (12) defining a waist opening (24) and a pair of leg openings (26),

a partially elastic, continuous waistborder (30) comprising four oppositely disposed elastic side segments (82) and at least one non-elastic segment (84, 86), and

a continuous, elastic waistband (32) joined to said partially elastic, continuous waistborder (30), **characterised in that** said waistband comprising at least one recoverable portion that is capable of being temporarily inhibited, and at least one elastic portion having an elasticity substantially the same as an elasticity of said elastic segments, said continuous elastic waistband being joined to said continuous waist border with said elastic portion joined to said elastic segment and said recoverable portion joined to said non-elastic segment.

2. The garment of claim 1 wherein said waistband (32) comprises a pair of side portions (88), a front portion (90), and a back portion (92),

said pair of side portions (88) being respectively joined to said pair of elastic side segments (82) of said waistborder (30),

one of said front portion (90) and said back portion (92) being operatively elastically joined to said non-elastic segment (84,86), said one portion (90,92) and said non-elastic segment (84,86) having an elasticity different from the elasticity of said elastic side segments (82).

3. The garment of one of the preceding claims comprising a pair of partially elastic, continuous legborders (38,108), and

a continuous, elastic legband (106) operatively elastically joined to each said partially elastic, continuous legborder.

4. A disposable garment comprising:

a pant body (12) comprising a continuous waistborder (30) defining a continuous waist opening (24),

said continuous waistborder (30) comprising at least one non-elastic segment (84,86) and at least one elastic segment (82), and

a continuous elastic waistband (32) **characterised in that** said waistband comprises at least one recoverable portion that is capable of being temporarily inhibited, and at least one elastic portion having an elasticity substantially the same as an elasticity of said elastic segment (82).

said continuous elastic waistband (32) being joined to said continuous waistborder (30) with said elastic portion joined to said elastic seg-

- ment (82), and said recoverable portion joined to said non-elastic segment (84,86),
- said recoverable portion, upon being activated, gathering said non-elastic segment (84,86). 5
5. The garment of claim 4 wherein said recoverable portion and said non-elastic segment (84,86), after being activated, have an elasticity different from the elasticity of said elastic segment (82). 10
6. The garment of one of claims 4 to 5 wherein said recoverable portion and said non-elastic segment (84,86), after being activated, have an elasticity substantially the same as the elasticity of said elastic segment (82) of said waistborder (30). 15
7. The garment of one of claims 4 to 5, wherein said recoverable portion and said non-elastic segment (84,86), after being activated, have an elasticity different from the elasticity of said elastic segment (82) of said waistborder (30). 20
8. The garment of one of the preceding claims wherein said waistband has a width between about 1 centimeter to about 8 centimeters. 25
9. The garment of one of the preceding claims wherein said waistband (32) is folded over an edge of said waistborder (30). 30
10. The garment of one of the preceding claims wherein said waistband (32) is C-folded upon itself.
11. The garment of one of the preceding claims wherein said waistband (32) extends beyond an edge of said waistborder (30). 35
12. The garment of one of the preceding claims, said garment comprising a topsheet (34), a backsheet (36) comprising said waistborder (30) and an absorbent structure (28) disposed on said backsheet (36). 40

Patentansprüche

1. Wegwerfbekleidungsstück mit einem Hosenkörper (12), welcher eine Tailleneöffnung (24) und ein Paar Beinöffnungen (26) festlegt, einer teilweise elastischen, kontinuierlichen Tailleneinfassung (30), welche vier entgegengesetzt angeordnete elastische Seitensegmente (82) aufweist und wenigstens ein unelastisches Segment (84,86), und 50
- einem kontinuierlichen, elastischen Taillenbund (32), welcher mit der teilweise elastischen, kontinuierlichen Tailleneinfassung (30) verbunden ist, da- 55

durch gekennzeichnet, dass

der Taillenbund wenigstens einen rückbildbaren Bereich aufweist, der zeitweise inaktiviert werden kann, und wenigstens einen elastischen Bereich, der eine Elastizität aufweist, die im wesentlichen einer Elastizität des elastischen Segments entspricht, wobei der kontinuierliche, elastische Taillenbund mit der kontinuierlichen Tailleneinfassung verbunden ist, wobei der elastische Bereich mit dem elastischen Segment verbunden ist und der rückbildbare Bereich mit dem unelastischen Segment verbunden ist.

2. Bekleidungsstück gemäß Anspruch 1, bei dem der Taillenbund (32) ein Paar Seitenbereiche (88), einen vorderen Bereich (90) und einen hinteren Bereich (92) aufweist, wobei das Paar Seitenbereiche (88) jeweils mit dem Paar elastischer Seitensegmente (82) der Tailleneinfassung (30) verbunden ist, wobei ein Bereich ausgewählt aus dem vorderen Bereich (90) und dem hinteren Bereich (92) wirksam mit dem unelastischen Segment (84,86) elastisch verbunden ist, wobei der eine Bereich (90,92) und das unelastische Segment (84,86) eine Elastizität aufweisen, welche sich von der Elastizität der elastischen Seitensegmente (82) unterscheidet.
3. Bekleidungsstück gemäß einem der vorhergehenden Ansprüche, welches ein Paar teilweise elastischer, kontinuierlicher Beineinfassungen (38, 108) aufweist, sowie einen kontinuierlichen, elastischen Beinbund (106), welcher wirksam mit jedem der teilweise elastischen, kontinuierlichen Beineinfassungen elastisch verbunden ist.
4. Wegwerfbekleidungsstück mit einem Hosenkörper (12), welcher eine kontinuierliche Tailleneinfassung (30) aufweist, die eine kontinuierliche Tailleneinfassung (30) festlegt, wobei die kontinuierliche Tailleneinfassung (30) wenigstens ein unelastisches Segment (84,86) und wenigstens ein elastisches Segment (82) aufweist, und 45
- einem kontinuierlichen, elastischen Taillenbund (32), **dadurch gekennzeichnet, dass** der Taillenbund wenigstens einen rückbildbaren Bereich aufweist, der zeitweise inaktiviert werden kann, sowie wenigstens einen elastischen Bereich, der eine Elastizität aufweist, die im wesentlichen einer Elastizität des elastischen Segments (82) entspricht, wobei der kontinuierliche, elastische Taillenbund (32) mit der kontinuierlichen Tailleneinfassung (30) verbunden ist, wobei der elastische Bereich mit dem elastischen Segment (82) verbunden ist und der rückbildbare Bereich mit dem unelastischen Segment (84,86) verbunden ist, 50

wobei der rückbildbare Bereich nach seiner Aktivierung das unelastische Segment (84,86) zusammenzieht.

5. Bekleidungsstück nach Anspruch 4, bei dem der rückbildbare Bereich und das unelastische Segment (84,86) nach der Aktivierung eine Elastizität aufweisen, welche sich von der Elastizität des elastischen Segments (82) unterscheidet. 5
6. Bekleidungsstück gemäß einem der Ansprüche 4 bis 5, bei dem der rückbildbare Bereich und das unelastische Segment (84,86) nach der Aktivierung eine Elastizität aufweisen, welche im wesentlichen der Elastizität des elastischen Segments (82) der Tailleneinfassung (30) entspricht. 10
7. Bekleidungsstück gemäß einem der Ansprüche 4 und 5, bei dem der rückbildbare Bereich und das unelastische Segment (84,86) nach der Aktivierung eine Elastizität aufweisen, welche sich von der Elastizität des elastischen Segments (82) der Tailleneinfassung (30) unterscheidet. 20
8. Bekleidungsstück gemäß einem der vorhergehenden Ansprüche, bei dem der Taillenbund (32) eine Breite von etwa 1 cm bis etwa 8 cm aufweist. 25
9. Bekleidungsstück gemäß einem der vorhergehenden Ansprüche, bei dem der Taillenbund (32) über eine Kante der Tailleneinfassung (30) hinweg gefaltet ist. 30
10. Bekleidungsstück gemäß einem der vorhergehenden Ansprüche, bei dem der Taillenbund C-förmig auf sich selbst gefaltet ist. 35
11. Bekleidungsstück gemäß einem der vorhergehenden Ansprüche, bei dem der Taillenbund (32) sich über eine Kante der Tailleneinfassung (30) hinaus erstreckt. 40
12. Bekleidungsstück gemäß einem der vorhergehenden Ansprüche, wobei das Bekleidungsstück eine Oberschicht (34), eine die Tailleneinfassung (30) aufweisende Rückschicht (36) sowie eine auf der Rückschicht (36) angeordnete saugfähige Struktur (28) umfasst. 45

Revendications

1. Vêtement jetable comprenant :

un corps de culotte (12) définissant une ouverture de ceinture (24) et une paire d'ouvertures de jambe (26),
un bord de ceinture (30) continu, partiellement

élastique, comprenant quatre segments latéraux élastiques (82) disposés en opposition et au moins un segment non élastique (84, 86), et une ceinture élastique continue (32) réunie audit bord de ceinture (30) continu partiellement élastique, **caractérisé en ce que** ladite ceinture comprend au moins une portion capable d'une récupération pouvant être temporairement inhibée, et au moins une portion élastique ayant une élasticité sensiblement identique à une élasticité desdits segments élastiques, ladite ceinture élastique continue étant réunie audit bord de ceinture continu avec ladite portion élastique réunie audit segment élastique, et avec ladite portion capable d'une récupération réunie audit segment non élastique.

2. Vêtement selon la revendication 1, dans lequel ladite ceinture (32) comprend une paire de portions latérales (88), une portion avant (90) et une portion arrière (92),

ladite paire de portions latérales (88) étant respectivement réunie à ladite paire de segments latéraux élastiques (82) dudit bord de ceinture (30),

l'une desdites portion avant (90) et portion arrière (92) étant réunie élastiquement et opérationnellement audit segment non élastique (84,86), ladite portion (90,92) réunie et ledit segment non élastique (84,86) ayant une élasticité différente de l'élasticité desdits segments latéraux élastiques (82).

3. Vêtement selon l'une des revendications précédentes, comprenant une paire de bords de jambe (38,108) continus et partiellement élastiques, et une bande de jambe (106) continue et élastique, réunie élastiquement et opérationnellement à chacun desdits bords de jambe continus et partiellement élastiques.

4. Vêtement jetable comprenant un corps de culotte (12) comprenant un bord de ceinture (30) continu définissant une ouverture de ceinture (24) continue, ledit bord de ceinture (30) continu comprenant au moins un segment non élastique (84, 86) et au moins un segment élastique (82), et une ceinture (32) élastique continue,

caractérisé en ce que ladite ceinture comprend au moins une portion capable d'une récupération pouvant être temporairement inhibée, et au moins une portion élastique ayant une élasticité sensiblement identique à une élasticité dudit segment élastique (82)

ladite ceinture (32) élastique continue étant réunie audit bord de ceinture (30) continu avec ladite portion élastique réunie audit segment élastique (82), et avec ladite portion capable d'une récu-

pération réunie audit segment non élastique (84, 86),

ladite portion capable d'une récupération fronçant, lorsqu'elle est activée, ledit segment non élastique (84, 86).

5

5. Vêtement selon la revendication 4, dans lequel ladite portion capable d'une récupération et ledit segment non élastique (84, 86) ont, après l'activation, une élasticité différente de l'élasticité dudit segment élastique (82). 10
6. Vêtement selon l'une des revendications 4 ou 5, dans lequel ladite portion capable d'une récupération et ledit segment non élastique (84, 86) ont, après l'activation, une élasticité sensiblement identique à l'élasticité dudit segment élastique (82) dudit bord de ceinture (30). 15
7. Vêtement selon l'une des revendications 4 ou 5, dans lequel ladite portion capable d'une récupération et ledit segment non élastique (84, 86) ont, après l'activation, une élasticité différente de l'élasticité dudit segment élastique (82) dudit bord de ceinture (30). 20 25
8. Vêtement selon l'une des revendications précédentes, dans lequel ladite ceinture a une largeur comprise entre environ 1 cm et environ 8 cm. 30
9. Vêtement selon l'une des revendications précédentes, dans lequel ladite ceinture (32) est repliée sur une lisière dudit bord de ceinture (30). 35
10. Vêtement selon l'une des revendications précédentes, dans lequel ladite ceinture (32) est repliée en C sur elle-même. 40
11. Vêtement selon l'une des revendications précédentes, dans lequel ladite ceinture (32) s'étend au-delà d'une lisière dudit bord de ceinture (30). 45
12. Vêtement selon l'une des revendications précédentes comprenant une feuille supérieure (34), une feuille support (36) comprenant ledit bord de ceinture (30) et une structure absorbante (28) disposée sur ladite feuille support (36). 50

50

55




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 7D




FIG. 8